

Blockade™ Cast Iron Bridge Plugs

Titan Division | Perforating Systems

Hunting's Blockade™ Bridge Plugs

Hunting's cast iron bridge plug is rated for high pressure applications up to 10,000 PSI and 350°F. The Blockade Bridge Plug is a bottom set plug that is used to isolate wellbore segments for stimulation/treatment or Plug and Abandonment. The plug will securely set in any hardness of casing and is designed to prevent preset while running into the hole.



Specifications

Cast Iron Bridge Plug					Casing Size	Setting Capability	
Bridge Plug Assembly	O.D. (in) [mm]	Shear (lbs) [kg]	Max Pressure (psi) [MPa]	Temperature (°F) [°C]	O.D. (in) [mm]	Max ID (in) [mm]	Minimum ID (in) [mm]
TSET-BP-4500-000	3.50 [88.9]	32,000 [14514.96]	10,000 [68.95]	350 [177]	4.50 [114.3]	4.090 [103.89]	3.826 [97.18]
TSET-BP-5500-000	4.24 [107.7]	32,000 [14514.96]	8,000 [55.16]	350 [177]	5.50 [139.7]	5.047 [128.19]	4.670 [118.62]

Part Numbers

Casing Size (in) [mm]	Bridge Plug Assembly No.	Tension Mandrel			Setting Sleeve		
		#10	#20	3.63 [92.2] 3.5 [88.9]	#10	#20	3.63 [92.2] 3.5 [88.9]
4.50 [114.3]	TSET-BP-4500-000	TSET-BP-1045-001	-	TSET-BP-3645-001	TSET-BP-1045-002	-	TSET-BP-3645-002
5.50 [139.7]	TSET-BP-5500-000	TSET-BP-1045-001	TSET-BP-2055-001	TSET-BP-3645-001	TSET-BP-1055-002	TSET-BP-2055-002	TSET-BP-3655-002

Disclaimer: Before continuing operations, always spot sand and/or cement on top of the bridge plug.

For more information contact your Titan Division sales representative today! Or visit us at: www.hunting-intl.com/titan

Contact Information

Sales
sales.titan@hunting-intl.com

Perforating
Pampa, TX USA
Milford, TX USA
Calgary, AB CAN

Instruments
Pampa, TX USA
Wichita Falls, TX USA
Houston, TX USA

Energetics
Milford, TX USA

Distribution
Hunting's distribution centers are strategically placed globally. For more information, visit us at: www.hunting-intl.com/titan